

I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

TestingResearchInnovation

### TEST REPORT

Page 1 of 10
Report No.: 2107100075 Date: 05-08-2021

Issued To:

M/s GEALAN PVT. LTD.

1ST FLOOR, DOOR NO. - 1-18/HIE/NE-2, HOLIDAY INN EXPRESS SUITS, NANAKRAMGUDA, GACHIBOWLI, RANGA REDDY TELANGANA - 50032

Sample Description : SLIDING FRAME 2 TRACK 60 MM SERIES

Sample Received Date : 10-07-2021 Sample Drawn By : Client


Specification : BS 476: Part-7:1997 & BS 476: Part 5:1979

Test Requested : Fire Resistance & Ignitability Test


Test Method : BS 476-Part-7:1997 & BS 476-Part-5:1979.

Test Result : Refer to Attached Pages.

#### SAMPLE PICTURE













Report No.:

I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com Testing

Research

Innovation

### TEST REPORT

Page 2 of 10 Date: 05-08-2021

I. FIRE TEST (as per Std. BS 476-part-7:1997)

2107100075

Fire Resistance Test Performed on: 12-07-2021 to 15-07-2021

**Sample Description:** 

Product: uPVC Profile (Sliding Frame 2 Track 60mm Series)

Specification: --

Sample Quantity: 02

Sample ID: 2107100075


Date of sample received: 10.07.2021

Date of Test Performed: 12.07.2021



"This test report is for the exclusive use of Atmy clients and is provided pursuant to the agreement between Atmy and its client. The laboratory will not be liable to any party, other than to the clients with the agreement, for any loss, expense or damage occasioned by the use of this report. Total liability of laboratory is limited to the invoiced amount only. This report cannot be used as evidence in a court of law without the written approval of Atmy".

# Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

TestingResearchInnovation

### TEST REPORT

Page 3 of 10
Report No.: 2107100075 Date: 05-08-2021

CONTENTS PAGE NO.

SUMMARY 04

TEST DETAILS 05


TEST RESULTS 06

CLASSIFICATION CRITERIA 07

CONCLUSION 07



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

Testing

Research

Innovation

TEST REPORT

Page 4 of 10 Date: 05-08-2021

#### 1.0 SUMMARY


Report No.:

2107100075


The objective of test was to determine of surface spread flame classification of the product "uPVC profile" in accordance with BS 476 Part – 7:1997. The test was performed in accordance with the procedures specified in the standard (BS 476 Part-7:1997) and the specimens were tested in the form of a composite. Test result of the product depicted that the sample tested has "Class -1" surface spread of flame in accordance with the class specified in the standard. The detailed results are summarized in the table-1.



The test results relate only to the behavior of the test specimens of the product under the particular conditions of test; they are not intended to be the sole criterion for assessing the potential fire Hazard of the product in use.



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory





# R ATMY ANALYTICAL LABS PVT.LTD. 1-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA

I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com



# **TEST REPORT**

Page 5 of 10
Report No.: 2107100075 Date: 05-08-2021

#### 2.0 TEST DETAILS

### 2.1 Conditioning of Specimen:

Prior to the test, the specimens were prepared and conditioned in accordance with standard at a temperature  $23 \pm 2^{\circ}$ C and relative humidity of  $50 \pm 5\%$ .


2.2 Form in which the specimens were tested: Composite

#### 2.3 Exposed faces:

The one face of the specimens was exposed to the heating conditions of the test.



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

TestingResearchInnovation

### TEST REPORT

Page 6 of 10 Date: 05-08-2021

#### 3.0 TEST RESULTS

Report No.: 2107100075


3.1 The test results for individual samples are given in Table-1 below:

т,	h	۱,	-1
Ιć	ah	ı	- 1

	Table - I					
Specimen No.	1	2	3	4	5	6
Spread of flame at first 1.5 minutes (mm)	55	58	55	57	54	57
Distance (mm)	Time of spread of flame to indicated distance (minutes : seconds)					
75 165 190 215 240 265 290 375 455 500 525 600 675 710 750 785 825						
Time of maximum spread of flame (minutes, seconds)	01:02	01:02	01:03	01:03	01:02	01:02
Distance of maximum spread of flame (mm)	69	69	70	70	70	69
Comments	None					



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

TestingResearchInnovation

# TEST REPORT

Page 7 of 10 Date: 05-08-2021

#### 4.0 CLASSIFICATION CRITERIA

Report No.: 2107100075

### 4.1 Classification of Surface spread of flame


Classification	Spread of flame	at 1.5 min.	Final spread of flame		
	Limit (mm)	Limit for one	Limit (mm)	Limit for one	
		specimen in		specimen in	
		sample (mm)		sample (mm)	
Class 1	165	165 + 25	165	165 + 25	
Class 2	215	215 + 25	455	455 + 45	
Class 3	265	265 + 25	710	710 + 75	
Class 4	Exceeding the limits for class 3				

#### **5.0 CONCLUSION:**

In accordance with the class definitions specified in the standard, the test results shows that the sample tested has "Class -1" surface spread of flame.



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

TestingResearchInnovation

### TEST REPORT

Page 8 of 10 Date: 05-08-2021

II. IGNITABILITY TEST (as per Std. BS 476:part 5:1979)

Ignitability Test Test Performed on: 02-08-2021 to 05-08-2021

#### **SAMPLE DESCRIPTION:**

Report No.: 2107100075

Product: uPVC Profile (Sliding Frame 2 Track 60mm Series)


Specification: --

Sample Quantity: 02


Sample ID: 2107100075

Date of sample received: 10.07.2021

Date of Test Performed: 05.08.2021



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

TestingResearchInnovation

# TEST REPORT

Page 9 of 10
Report No.: 2107100075 Date: 05-08-2021

#### **TEST PURPOSE:**


To determine the ignitability characteristics of the exposed surface of essentially flat, rigid or semi-rigid building materials, UPVC profile or composites, when tested in the vertical position to the specified in British Standard 476: Part 5:1979 "Method of test for ignitability".

#### **TEST CONDITIONING:**

Three specimens were conditioned for 48 hours at temp.23±2°C and relative humidity 50±5%.



#### Govt. Approved Laboratory ISO 9001: 2015, ISO 14001:2015 & OHAS 1800:2007 Certified Laboratory







I-30, DLF Industrial Area, Phase-1, Faridabad (Haryana) INDIA Phone: +91-129-4019544 info@atmylabs.com, www.atmylabs.com

Testing

Research

Innovation

### **TEST REPORT**

Page 10 of 10 Date: 05-08-2021

#### **OBSERVATION:**

Report No.: 2107100075

Description	Specimens			Requirement	Conformity
	1	2	3		
1.Time of flaming removal of test flame	0	0	0	Not more than 10 sec.	Yes
2. Burning of the test specimen extending to the edges	No	No	No	Do not extent to any edge during flame application or within 10 sec period after removal of the test flame.	Yes

REMARKS: The above sample conforms to as per BS 476: Part 5: 1979 with respect to above test.

-----End of Report---

D. Kumar **QUALITY MANAGER** 

**Authorised Signatory** 





